

PNEUMATIC

Air Wrench / Air Screwdriver / Air Grinder / Air Hammer





Air Wrench



■ 3/8" Air Ratchet Wrench

Item No.	Overall Length		KGS
771-101	254 mm	1	1.2
Square Drive : 3/8"			
Max. Torque : 90 ft-lb			
Free Speed : 160 RPM			
Air Consumption : 3.7 cfm			
Air Inlet Thread : 1/4" PT/NP			



■ 1/2" Air Ratchet Wrench

Item No.	Overall Length		KGS
771-102	254 mm	1	1.25
Square Drive : 1/2"			
Max. Torque : 90 ft-lb			
Free Speed : 160 RPM			
Air Consumption : 3.7 cfm			
Air Inlet Thread : 1/4" PT/NP			



■ 3/8" Butterfly Air Wrench

Item No.	Overall Length		KGS
770-816	171 mm	1	1.1
Square Drive : 3/8"			
Max. Torque : 75 ft-lb			
Free Speed : 10,000 RPM			
Actual Air Consumption : 19 cfm			
Average Air Consumption : 4.7 cfm			
Recommended Air Pressure : 90 psi (6.3 Bar)			
Minimum Hose Size : 3/8" (10 mm)			



Light
Weight

Twin Hammer

■ 3/8" Exquisite Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-800	3 speed	3 speed	125 mm	1	1.55
Square Drive : 3/8"					
Torque Range : 25-260 ft-lb					
Max. Torque : 500 ft-lb					
Free Speed : 10,000 RPM					
Air Consumption : 5.8 cfm					
Air Inlet Thread : 1/4" PT/NP					
Noise Level : 86 dB					
Vibration : 3.1 m/s ²					

Air Wrench



Light
Weight
Twin Hammer

■ 1/2" Exquisite Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
----------	---------	---------	----------------	--	-----

771-810	3 speed	3 speed	125 mm	1	1.6
---------	---------	---------	--------	---	-----

Square Drive : 1/2"

Torque Range : 25-260 ft-lb

Max. Torque : 450 ft-lb

Free Speed : 10,000 RPM

Air Consumption : 5.8 cfm

Air Inlet Tread : 1/4" PT/NP

Noise Level : 86 dB

Vibration : 3.1 m/s²



Twin Hammer

■ 1/2" Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
----------	---------	---------	----------------	--	-----

771-809	5 speed	1 speed	184 mm	1	2.64
---------	---------	---------	--------	---	------

Square Drive : 1/2"

Torque Range : 25-330 ft-lb

Max. Torque : 620 ft-lb

Free Speed : 7,200 RPM

Air Consumption : 16.8 cfm

Air Inlet Tread : 1/4" NPT-18, 1/4" PT-19

Noise Level : 90 dB



Twin Hammer

■ 1/2" Air Impact Wrench – Compact

Item No.	Forward	Reverse	Overall Length		KGS
----------	---------	---------	----------------	--	-----

771-815	5 speed	1 speed	146 mm	1	2.2
---------	---------	---------	--------	---	-----

Square Drive : 1/2"

Torque Range : 25-500 ft-lb

Max. Torque : 800 ft-lb

Free Speed : 7,500 RPM

Air Consumption : 5.0 cfm

Air Inlet Tread : 1/4" NPT-18, 1/4" PT-19

Noise Level : 85 dB



More Power
Less Weight.

Twin Hammer

■ 1/2" Heavy Duty Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
----------	---------	---------	----------------	--	-----

771-813	3 speed	3 speed	170 mm	1	2.45
---------	---------	---------	--------	---	------

Square Drive : 1/2"

Torque Range : 25-620 ft-lb

Max. Torque : 1,000 ft-lb

Free Speed : 7,500 RPM

Air Consumption : 5.8 cfm

Air Inlet Tread: 1/4" NPT-18, 1/4" PT-19

Noise Level : 86 dB

1 SOCKETS

2 WRENCHES

3 SCREWDRIVERS

4 HEX WRENCH

5 FASTENER
DRIVE TOOLS

6 HAND TOOLS

7 STORAGE

8 PNEUMATIC

9 DIAMOND
WHEELS

10 CORE BITS

11 HOLE SAWS

12 ABRASIVES



Air Wrench



Twin Hammer

1/2" High Performance Twin Hammer Air Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-832	3 speed	3 speed	128 mm	1	1.6

Square Drive : 1/2"

Max. Torque : 1,000 ft-lb

Free Speed : 8,500 RPM

Air Consumption : 9.1 cfm

Air Inlet Thread : 1/4" NPT-18, 1/4" PT-19

Noise Level : 86 dB

Vibration : 3.1 m/s²



More Power
Less Weight.

Twin Hammer

3/4" Heavy Duty Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-814	3 speed	3 speed	170 mm	1	2.5

Square Drive : 3/4"

Torque Range : 25-640 ft-lb

Max. Torque : 1,100 ft-lb

Free Speed : 7,500 RPM

Air Consumption : 11.8 cfm

Air Inlet : 1/4" PT/NP



Twin Hammer

3/4" Heavy Duty Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-834	3 speed	3 speed	126 mm	1	4.2

Square Drive : 3/4"

Max. Torque : 1,500 ft-lb

Free Speed at 90 psi : 8,000 RPM

Air Inlet Thread : 1/4" NPT-18, 1/4" PT-19

Minimum Hose Size : 3/8"

Noise Level : 90 dB



Twin Hammer

3/4" Air Impact Wrench – Composite

Item No.	Forward	Reverse	Overall Length		KGS
771-833	2 speed	2 speed	126 mm	1	2.1

Square Drive : 3/4"

Max. Torque : 1,000 ft-lb

Free Speed at 90 psi : 8,000 RPM

Air Inlet Thread : 1/4" NPT-18, 1/4" PT-19

Minimum Hose Size : 3/8"

Air Consumption : 6.3 cfm

Air Wrench



■ 1" Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-835	1 speed	1 speed	350 mm	1	6.6

Square Drive : 1"

Anvil : 1/2"

Working Torque : 1,000 ft-lb (1,400 Nt-m)

Max. Torque : 1,500 ft-lb (2,000 Nt-m)

Free Speed : 4,000 RPM

Air Consumption : 15 cfm

Air Inlet Thread : 3/8" PT

Noise Level : 102 dB

Vibration : 13.93 m/s²



■ 1" Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-836	3 speed	3 speed	500 mm	1	7.4
771-838	3 speed	3 speed	550 mm	1	7.6

Square Drive : 1"

Anvil : (771-836) 6-1/2" (771-838) 8"

Torque Range : 1,000 ft-lb (1,400 Nt-m)

Max. Torque : 1,500 ft-lb (2,000 Nt-m)

Free Speed : 4,000 RPM

Air Consumption : 15 cfm

Air Inlet Thread : 3/8" PT

Noise Level : 102 dB

Vibration : 13.93 m/s²



Pin Less
Side Exhaust

■ 1" Air Impact Wrench

Item No.	Forward	Reverse	Overall Length		KGS
771-808	1 speed	1 speed	629 mm	1	14.5

Square Drive : 1"

Anvil : 8"

Max. Torque : 2,000 ft-lb (2,712 Nt-m)

Free Speed : 2,400 RPM

Air Consumption : 8.5 cfm

Air Inlet Thread : 1/2" PT

1 SOCKETS

2 WRENCHES

3 SCREWDRIVERS

4 HEX WRENCH

5 FASTENER
DRIVE TOOLS

6 HAND TOOLS

7 STORAGE

8 PNEUMATIC

9 DIAMOND
WHEELS

10 CORE BITS

11 HOLE SAWS

12 ABRASIVES



1/2" Dr. Impact Wrench & Socket Set – 14 Pc.

Item No.		Blow Case		KGS
774-010	Metric	38 x 29 x 9 (H) cm	1	5.42

- 1/2" Dr. Air Impact Wrench 771-809
- 10 Impact Sockets : 9, 10, 11, 13, 14, 17, 19, 22, 24, 27 mm
- Impact Universal Joint
- Impact Extension : 3"
- Air Inlet : 1/4"



1/2" Dr. Impact Wrench & Socket Set – 15 Pc.

Item No.		Blow Case		KGS
774-011	Metric	38 x 29 x 9 (H) cm	1	4.25

- 1/2" Dr. Exquisite Air Impact Wrench 771-810
- 11 Impact Sockets : 9, 10, 11, 12, 13, 14, 17, 19, 22, 24, 27 mm
- Impact Universal Joint
- Impact Extension : 3"
- Air Inlet : 1/4"



1/2" Dr. Impact Wrench & Socket Set – 25 Pc.

Item No.		Blow Case		KGS
774-012	Metric	38 x 29 x 9 (H) cm	1	5.36

- 1/2" Dr. Exquisite Air Impact Wrench 771-810
- 10 Impact Sockets : 9, 10, 12, 13, 14, 17, 19, 22, 24, 27 mm
- 6 Hex Head Impact Sockets : H5, H6, H7, H8, H10, H12
- 5 TORX® Head Impact Sockets : T30, T40, T45, T50, T55
- Impact Universal Joint
- Impact Extension : 3"
- Air Inlet : 1/4"

Air Hammer



■ Air Hammer

Item No.	Overall Length		KGS
771-221	225 mm	1	1.6

Blow Per Minute : 2,200
 Shank Opening : Round
 Stroke Length : 89 mm
 Chisel Shank Diameter : 0.401" (10.2 mm)
 Air Inlet : 1/4"
 Air Inlet Pressure : 90-120 psi
 Vibration Loaded at 18 kgf : 9.4 m/s²
 Air Consumption : 14 cfm



771-222	175 mm	1	1.4
---------	--------	---	-----

Blow Per Minute : 3,200
 Shank Opening : Round
 Stroke Length : 67 mm
 Chisel Shank Diameter : 0.401" (10.2 mm)
 Air Inlet : 1/4"
 Air Inlet Pressure : 90-120 psi
 Vibration Loaded at 18 kgf : 14.9 m/s²
 Air Consumption : 15 cfm



■ Hitch Cutter Retainer

Item No.		KGS
771-242	1	0.12

Hitch Cutter Retainer for Air Hammer



■ 9 Pc. Air Hammer Set

Item No.		KGS
771-007	1	3.4

- Air Hammer 771-221
- Hitch Cutter Retainer
- Spring Retainer
- Air Inlet : 1/4"
- 5 Pc. Air Impact Chisel (178 mm) :
 - ▶ Spot Weld Breaker
 - ▶ Fishtail
 - ▶ Notch
 - ▶ Flat
 - ▶ Marker Point



Air Grinder, Air Screwdriver, Air Saw



1/4" Air Die Grinder

Item No.	Overall Length		KGS
771-905	178 mm	1	0.60

RPM : 22,000

Collect Size : 1/4" (6 mm), 1/8" (3 mm)

Air Consumption : 3.5 cfm

Air Inlet Tread : 1/4" PT or NPT

Min. Hose size : 3/8"

Noise Level : 80 dB



771-906	5" Extension	280 mm	1	0.8
---------	--------------	--------	---	-----

RPM : 22,000

Collect Size : 1/4" (6 mm), 1/8" (3 mm)

Air Consumption : 3.5 cfm

Air Inlet Tread : 1/4" PT or NPT

Min. Hose size : 3/8"

Noise Level : 80 dB



1/4" Air Screwdriver

Item No.		KGS
770-802	1	0.7

Shank : 6.35 mm

Max. Torque : 55 Nt-m

Free Speed : 9,000 RPM

Air Consumption : 9 cfm

Air Inlet Thread : 1/4" PT

Capacity : 4-5 mm



Air Body Saw (Air File)

Item No.	Overall Length		KGS
771-201	147 mm	1	0.4

Cutting Capability To Steel Sheet : 4 mm

Air Inlet Thread : 1/4" PT (1/4" NPT)

Vibration : 3 m/s²

Stroke Length : 10 mm

Sound Pressure : 80 dB

Saw Blade : 32T / 24T

Blow Per Minute : 12,000

Average Air Consumption : 5.8 cfm

Hose Size : 3/8"



771-202	215 mm	1	0.55
---------	--------	---	------

Cutting Capability To Steel Sheet : 4 mm

Air Inlet Thread : 1/4" NPT (1/4" PT)

Vibration : 3 m/s²

Stroke Length : 10 mm

Sound Pressure : 80 dB

Saw Blade : 32T / 24T

Blow Per Minute : 10,000

Average Air Consumption : 5.75 cfm

Hose Size : 3/8"

Spray Gun, Sander



Aluminum Cup



POM Plastic Cup



Aluminum Cup



POM Plastic Cup



Air Spray Gun, W100, Gravity

Item No.	Fluid Tip Size	with Cup		KGS
770-723	1.5 mm Adjustable	400 c.c.	1	0.52
■ Height / Length : 172mm / 149mm		■ Weight : Spary Gun 323g, Cup 190g		
● Suitable Air Pressure : 34 - 48 psi		● Air Inlet : PF 1/4" -19		
● Pattern Width : 8" (200 mm)		● Air Consumption : 145 l/min		
● Paint Delivery : 200 cc/min		● Nozzle to Work Surface : 6-9"		

Air Spray Gun, W100, Gravity


Item No.	Fluid Tip Size	with Cup		KGS
770-726	1.5 mm Adjustable	400 c.c.	1	0.47
■ Height / Length : 172mm / 149mm		■ Weight : Spary Gun 323g, Cup 142g		
● Suitable Air Pressure : 34 - 48 psi		● Air Inlet : PF 1/4" -19		
● Pattern Width : 8" (200 mm)		● Air Consumption : 145 l/min		
● Paint Delivery : 200 cc/min		● Nozzle to Work Surface : 6-9"		

Air Spray Gun, W100, Siphon Feed

Item No.	Fluid Tip Size	with Cup		KGS
770-728	1.5 mm Adjustable	750 c.c.	1	0.52
■ Height / Length : 172mm / 149mm		■ Weight : Spary Gun 319g, Cup 203g		
● Suitable Air Pressure : 35 - 50 psi		● Air Inlet : PF 1/4" -19		
● Pattern Width : 7" (175 mm)		● Air Consumption : 145 l/min		
● Paint Delivery : 175 cc/min		● Nozzle to Work Surface : 6-9"		

Air Spray Gun, HVLV, Gravity

Item No.	Fluid Tip Size	with Cup		KGS
770-730	1.3, 1.5, 1.7, 2.0 mm	600 c.c.	1	0.69
■ Height / Length : 330mm / 145mm		■ Weight : Spary Gun 540g, Cup 154g		
● Suitable Air Pressure : 29 - 42 psi		● Air Inlet : 1/4" NPS (Male)		
● Pattern Width : 10 - 12" (250-300 mm)		● Air Consumption : 14.0 cfm@40psi		
● Paint Delivery : 180 cc/min		● Nozzle to Work Surface : 6-9"		



Random Orbital Sander

Item No.		KGS
771-001	1	0.4
● Pad Size : 5"		● Orbit Diameter : 5mm
● Free Speed : 10,500 RPM		● Operation Air Pressure : 90 psi (6.3 bar)
		● Air Inlet Hose Size : 3/8"

